

TECHNICAL DATA SHEET

version 03/2024



MUFFØUT PROFUMATO

Cleaner with whitening action for the elimination of halos or black stains









DESTINATION → **Porous surfaces in natural stone and building artifacts**, painted and unpainted walls, both indoors and outdoors. Always check the compatibility of the product with the material.

PROPERTIES → MUFFØUT PROFUMATO is a specific product for the rapid elimination of superficial black stains and halos.

The product performs a **whitening action in a few minutes**. It's particularly suitable for cleaning interventions **before repainting**. Its selective action acts only on the stains, without affecting or altering the material in any way. Scented formulation.

USE → On surfaces where stratified black dirt stains are present, brush the surface in order to remove the most superficial layers and allow a better and faster action of the product. Then apply MUFFØUT PROFUMATO, by spraying it on the surface to be cleaned from a distance of about 20 cm. Leave the product to act for about 5-10 minutes. Repeat the above operations if necessary.

It is advisable to carry out preliminary tests on the surfaces to be treated in order to avoid possible unwanted effects. The product has no cleaning power against grease and oil stains.

STORAGE → The product must be stored in its original containers, well sealed, away from light, in a cool environment and away from direct heat sources, at temperatures between + 5 °C and + 25 °C. Under these conditions, the product is stable for 12 months. The product must be stored in environments where the ambient temperature does not exceed 25 °C, to prevent the swelling of the containers caused by the chlorine component contained within the product.

YIELD → As an indication, 3-6 m² per liter of product.

TECHNICAL DATA

→ APPEARANCE: yellowish liquid

⇒ pH: 13 ± 0,5

⇒ SPECIFIC WEIGHT: 1,2 Kg/l ± 0,1

PACKAGING

1CR512L05 → 12 x 500 ml PLASTIC BOTTLE with sprayer

WARNINGS

- → Product intended for professional use.
- → Operating temperature: + 5 ° C / + 35 ° C.
- → Do not apply in conditions of impending rain.
- → Equip the operators as required by current safety regulations.
- → Properly ventilate closed rooms while using the product.

All information contained in our records correspond to our best knowledge of current techniques and cannot be considered binding or challenging as the real application conditions, verifiable case, may also result in major changes of both practices described above and the results obtained. Perform preliminary tests to determine if the product is suitable for the intended or not. We decline any liability for any damage resulting from improper use or misuse of the product. Do not litter in the environment. This data sheet replaces all previous versions.