



MUFFØUT

Product with bleaching action for the elimination of halos or black spots on surfaces



DESTINATION → Porous surfaces in natural stone and artifacts in general, painted or not, both indoor and outdoor. Always check the compatibility of the product with the support.

PROPERTIES → Specific product for the **rapid elimination of black superficial spots**.

The product performs a **bleaching action** in a few minutes. Particularly suitable for cleaning interventions before repainting. Its selective action acts only on the stain, without affecting or altering the support in any way.

USE → On substrates where stratified black dirt is present, **brush the surface in order to remove the more superficial layers** and allow a better and faster action of the product. Then apply **MUFFØUT**, **spraying it onto the surface to be cleaned from a distance of about 20 cm**. Allow the product to **work for about 5-10 minutes**, repeat the above operations if necessary.

It is advisable to carry out preliminary tests on the surfaces to be treated in order to avoid possible undesired effects. The product has no cleaning action against stains caused by oily or greasy substances.

STORAGE → The product must be stored **in its original containers, well sealed, away from light**, in a cool place away from direct heat sources at **temperatures between + 5 ° C and + 25 ° C**. Under these conditions, **the product is stable for 12 months**. The product must be stored in environments where the temperature does not exceed 25 ° C, to prevent the chlorine component contained in the product from causing the packaging to swell due to heat.

YIELD → As an indication only, **3-6 m² / lt** of product.

TECHNICAL DATA

- **APPEARANCE:** yellowish liquid
- **pH:** 13 ± 0,5
- **SPECIFIC WEIGHT:** 1,2 Kg/l ± 0,1

PACKAGING

- 1CR513L05** → 12 x 500 ml plastic **SPRAY BOTTLE**
- 1CR513L5** → 2 x 5 liters plastic **TANK**

WARNINGS

- Product intended for professional use.
- Use temperature: + 5 ° C / + 35 ° C
- Do not apply in conditions of impending rain.
- Equip operators as required by current safety regulations.
- Ventilate closed rooms adequately while using the product.

All information contained in our records correspond to our best knowledge of current techniques and cannot be considered binding or challenging as the real application conditions, verifiable case, may also result in major changes of both practices described above and the results obtained. Perform preliminary tests to determine if the product is suitable for the intended or not. We decline any liability for any damage resulting from improper use or misuse of the product. Do not litter in the environment. This data sheet replaces all previous versions.